



FIELD COMM GROUP™

*Connecting the World of
Process Automation*



COMMUNICATION PROTOCOL

**Common Practice Command
Test Specification**

**HCF_TEST-004, FCG TT20004
Revision 6.1**

Release Date: 16 November 2020

Release Date: 16 November 2020

Document Distribution / Maintenance Control / Document Approval

To obtain information concerning document distribution control, maintenance control and document approval, please contact the FieldComm Group at the address shown below.

Copyright © 2000, 2002, 2004, 2009, 2018, 2020 FieldComm Group

This document contains copyrighted material and may not be reproduced in any fashion without the written permission of the FieldComm Group.

Trademark Information

HART[®] and WirelessHART[®] are registered trademarks of the FieldComm Group, Austin, Texas, USA. Any use of the term HART or WirelessHART hereafter in this document, or in any document referenced by this document, implies the registered trademark. All other trademarks used in this or referenced documents are trademarks of their respective companies. For more information contact the FieldComm Group Staff at the address below.



FIELDCOMM GROUP™

*Connecting the World of
Process Automation*

FieldComm Group
9430 Research Boulevard
Suite 1-120
Austin, TX 78759, USA

Voice: +1 512-792-2300
FAX: 1-512-792-2310

<http://www.fieldcommgroup.org>

Use of imperatives in HART Specifications

The key words (imperatives) "must", "required", "shall", "should", "recommended", "may", and "optional" when used in this document are to be interpreted as follows:

- Must** **Must, Shall, or Required** denotes an absolute mandatory requirement. For example, "All HART Field Devices must implement all Universal Commands"
- Should** **Should or Recommended** indicates a requirement that, given good cause/reason, can be ignored. However, the consequences of ignoring the requirement must be fully understood and well justified before doing so.
- May** **May or Optional** identifies a requirement that is completely optional and can be supported at the discretion of the implementation. May can be used to identify optional Host Application or Master functionality and, when this is the case, does not imply the function is optional in Field Devices.

Intellectual Property Rights

The FieldComm Group does not knowingly use or incorporate any information or data into the HART Specifications which the FieldComm Group does not own or have lawful rights to use. Should the FieldComm Group receive any notification regarding the existence of any conflicting Private IPR, the FieldComm Group will review the disclosure and either (a) determine there is no conflict; (b) resolve the conflict with the IPR owner; or (c) modify this specification to remove the conflicting requirement. In no case does the FieldComm Group encourage implementers to infringe on any individual's or organization's IPR.

Table of Contents

Preface	7
Introduction.....	8
1. Scope.....	10
1.1 Features Tested	10
1.2 Features Not Tested	10
2. References.....	11
2.1 The HART-Field Communications Protocol Specifications	11
2.2 Other FieldComm Group Documents.....	11
2.3 Related Documents.....	11
3. Definitions	12
4. Symbols/Abbreviations	13
5. Approach.....	14
5.1 Testing Sequence	15
5.2 Conventions	16
5.3 Burst Mode Services	17
5.4 Comparing Floating-Point Numbers	18
6. Test Definitions	19
6.1 CAL000 Check for Common Practice Commands	19
6.2 CAL001 Verify Write Protect	23
6.3 CAL033 Read Device Variables.....	48
6.4 CAL034 Write Primary Variable Damping Value.....	51
6.5 CAL035 Write Primary Variable Range Values.....	55
6.6 CAL036 Set Primary Variable Upper Range Value.....	62
6.7 CAL037 Set Primary Variable Lower Range Value.....	65
6.8 CAL039 (Reserved)	68
6.9 CAL040 Enter/Exit Fixed Current Mode	69
6.10 CAL041 Perform Self Test.....	73
6.11 CAL042 Perform Device Reset.....	74
6.12 CAL043 Set Primary Variable Zero	76
6.13 CAL044 Write Primary Variable Units.....	78
6.14 CAL045 Trim Loop Current Zero	81
6.15 CAL046 Trim Loop Current Gain	84
6.16 CAL047 Write Primary Variable Transfer Function.....	87
6.17 CAL049 Write Primary Variable Transducer Serial Number.....	89
6.18 CAL050 Read Dynamic Variable Assignments	91
6.19 CAL051 Write Dynamic Variable Assignments.....	92
6.20 CAL052 Set Device Variable Zero.....	96
6.21 CAL053 Write Device Variable Units	99
6.22 CAL054 Read Device Variable Information	102

6.23	CAL055 Write Device Variable Damping Value.....	104
6.24	CAL056 Write Device Variable Transducer Serial Number	109
6.25	CAL057 (Reserved).....	112
6.26	CAL058 (Reserved).....	112
6.27	CAL059 (Reserved).....	112
6.28	CAL060 Read Analog Channel And Percent Of Range	113
6.29	CAL061 (Reserved).....	114
6.30	CAL062 Read Analog Channels.....	115
6.31	CAL063 Read Analog Channel Information.....	116
6.32	CAL064 Write Analog Channel Additional Damping Value	117
6.33	CAL065 Write Analog Channel Range Values	121
6.34	CAL066 Enter/Exit Fixed Analog Channel Mode.....	128
6.35	CAL067 Trim Analog Channel Zero.....	132
6.36	CAL068 Trim Analog Channel Gain	136
6.37	CAL069 Write Analog Channel Transfer Function.....	140
6.38	CAL070 Read Analog Channel Endpoint Values	143
6.39	CAL071 Lock Device	144
6.40	CAL072 Squawk	151
6.41	CAL073 Find Device.....	154
6.42	CAL074 Verify I/O System Commands	156
6.43	CAL078 Command Aggregation.....	168
6.44	CAL079 Write Device Variable	171
6.45	CAL080 Verify Device Variable Trim Commands.....	174
6.46	CAL091 Trending.....	180
6.47	CAL101 I/O Subsystem Burst Mode.....	190
6.48	CAL103 Support for Multiple Burst Messages.....	197
6.49	CAL104 Smart Data Publishing	206
6.50	CAL107 Write Burst Device Variables.....	213
6.51	CAL108 Write Burst Mode Command Number.....	217
6.52	CAL109 Burst Mode Control.....	222
6.53	CAL110 (Reserved).....	227
6.54	CAL115 Event Notification.....	228
6.55	CAL512 Country Code.....	243
6.56	CAL518 Location Description	245
6.57	CAL520 Process Unit Tag	248
6.58	CAL523 Read Condensed Status Mapping Array	251
6.59	CAL524 Manipulating Condensed Status Map.....	261
6.60	CAL526 Status Simulation.....	274
ANNEX A. Reusable Test Procedure Definitions		288
A.1	CheckCommandImplemented (Cmd)	288
A.2	CheckBurstCommands ()	288
A.3	CheckForCommand (Cmd).....	289
A.4	CheckForRecommendedCommand (Cmd)	289
A.5	CheckReadyForBurst ()	290

A.6	CompareAnalogChannelValue (aChan, aValue, FAILUREPOINT).....	291
A.7	CyclePower ()	292
A.8	DisableBurstMode (bMsg)	292
A.9	EnableBurstMode (bMsg)	293
A.10	FindNextAnalogChannel (aChan).....	293
A.11	FindNextDeviceVariable (dVar)	294
A.12	IdentifyDevice ().....	296
A.13	IssueCommand103 (bmsg, period, maxperiod, failurepoint).....	296
A.14	IssueCommand104 (bmsg, trigger, classification, units, value, failurepoint)	297
A.15	IssueCommand109 (bMsg, bCtrl).....	297
A.16	IssueCommand524 (index, noEntries, mappingCodes [])	298
A.17	IssueCommand525 ()	298
A.18	IssueCommand526 (modeCode).....	299
A.19	IssueCommand527 (bitNo, simVal)	300
A.20	OnlyFSet (fp)	300
A.21	OnlyCSet (fp)	301
A.22	OnlySSet (fp)	301
A.23	OnlyMSet (fp).....	302
A.24	ReadCondensedStatusMap (StatusMap []).....	302
A.25	ReadPV ().....	303
A.26	TestValidFrame ().....	303
A.27	VerifyLoopCurrent (v, failurepoint).....	303
A.28	VerifyNotLocked ().....	304
A.29	VerifyNotWriteProtected ().....	304
A.30	VerifyRangeAndPV (lrv, urv, units, PV, FAILUREPOINT).....	305
A.31	VerifyResponseAndByteCount (r, b).....	305
A.32	VerifyAssociatedCommands (Cmd[0], Cmd[1], Cmd[2]...).....	306
ANNEX B. Failure Point Cross Reference		307
ANNEX C. Revision History		311
C.1	Changes from Revision 6.0 to 6.1	311
C.2	Changes from Revision 5.0 to 6.0	311
C.3	Changes from Revision 4.0 to 5.0	312
C.4	Changes from Revision 3.0 to 4.0	313
C.5	Changes from Revision 2.0 to 3.0	314
C.6	Changes from Revision 1.0 to 2.0	314